


SUPPORT

OUTERRING



Stock #	CAPACITY lb N		THREAD
FSH00149	20K	88960	1 1/4 -12
FSH01354			M33 X 2
FSH00150	30K	133400	1 1/4 -12
FSH01355			M33 X 2
FSH00151	50K	222400	1 1/4 -12
FSH00954			M33 X 2

SPECIFICATIONS:

RATED OUTPUT 2 mV/V nom. 150% of R.O. SAFE OVERLOAD ZERO BALANCE ±1% of R.O. 20 MAX EXCITATION (VDC OR VAC) 350 Ω **BRIDGE RESISTANCE**

NONLINEARITY ±0.1% of R.O. ±0.1% of R.O. HIGHER SPECIFICATIONS OF 0.05% AVAILABLE ±0.2% of R.O. CONTACT FACTORY

HYSTERESIS

NONREPEATABILITY ±0.02% of R.O. ±0.02% of LOAD CREEP

±0.001% of R.O./°F [0.0018% of R.O./°C] TEMP. SHIFT ZERO ±0.002% of LOAD/°F [0.0036% of LOAD/°C] TEMP. SHIFT SPAN

60 to 160°F [15 to 72°C] COMPENSATED TEMP. -60 to 200°F [-50 to 93°C] OPERATING TEMP. 17-4PH / ALLOY STEEL MATERIAL

WEIGHT 9lb [4.1kg]

0.002 to 0.005 [0.05 to 0.13] nom. **DEFLECTION**

CONNECTOR: 6 Pin BENDIX Receptacle (PT02A-10-6P) ACCESSORIES AND RELATED INSTRUMENTS AVAILABLE

CALIBRATION (STD) 5pt. COMPRESSION; 60.4 K \(\Omega \) SHUNT CAL. VALUE

CALIBRATION TEST EXCITATION 10 VDC





SCIGATE AUTOMATION (S) PTE LTD

No.1 Bukit Batok Street 22 #01-01 Singapore 659592 Fax: (65) 6562 0588 Email: sales@scigate.com.sg Web: www.scigate.com.sg

Business Hours: Monday - Friday 8.30am - 6.15pm

OTHER AVAILABLE RECEPTACLES & MATING CONNECTORS

BENDIX RECEPTACLE (PCO4E-10-6P) BENDIX MATING CONNECTOR (PCO6E-10-6S-SR)

BENDIX RECEPTACLE (PTO2H-10-6P)

BENDIX MATING CONNECTOR (PTO6A-10-6S-SR)



This drawing is submitted solely for the information and exclusive use of the original addressee. It is not to be divulged in whole or in part, by any firm or individual without written permission from FUTEK

10 THOMAS IRVINE, CA 92618 USA 1-800-23-FUTEK (38835)

INTERNET: http://www.futek.com