



ACCESSORIES

thermal printers

DP 24

High-performance thermal desktop printer , 60mm paper width

High speed printing up to 140mm/sec

Model with internal power supply

Easier paper loading with front access and autoloading

Cutter -optional-

Interfaces: RS232 and RS485

All models available with cash drawer and drivers (Windows and Linux)

Prints the most common barcode: UPC-A, UPC-E, EAN 13, EAN 8, CODE 39, ITF, CODABAR, CODE 128, CODE 32, PHARMACEUTICAL, CODE 93

Prints on thermal paper -double color-

TECHNICAL CHARACTERISTICS DP 24

Printing method:	thermal line printing
Resolution:	203 dpi (8dots/mm)
Printing speed (mm/sec):	110 High Quality, 140 High Speed
Character set:	ASCII standard, International
Type styles:	normale, double and quadruple height and width, reverse, underscored, italic, bold
Printing direction:	straight 180°
Paper width:	60 ± 0.5 mm
Roll dimension:	65mm max dim.
Emulation:	CUSTOM/POS
Interface:	RS232
Data buffer:	8 KB
Flash memory:	256 KB
Graphic memory:	3 logos of 32 KB
Drivers:	Win 2K, XP, Linux
Power consumption:	0.5 A*
Power:	90-240 Vac, 50/60 Hz
DKD function:	1 Driver
MTBF:	180.000 hours **
Safety:	EN60950 2001
Dimensions:	170x120x100 mm (h=110mm with cutter)
Weight:	0.6 Kg



SCIGATE AUTOMATION (S) PTE LTD

No.1 Bukit Batok Street 22 #01-01 Singapore 659592

Tel: (65) 6561 0488

Fax: (65) 6562 0588

Email: sales@scigate.com.sg

Web: www.scigate.com.sg

Business Hours: Monday - Friday 8.30am - 6.15pm

