



ACCESSORIES

thermal labeller

LP542S

Direct thermal labeller with peel-off as standard
Quick emission of labels
High print resolution
Compact size
Ideal for printing in any industrial environment

TECHNICAL CHARACTERISTICS LP542S

Print Method:	direct thermal
Print resolution:	203 dpi (8 dots/mm)
Print speed:	up to 127 mm/s
Maximum print length:	1016 mm
Maximum print width:	108 mm
Label length:	from 10 mm to 999 mm
Label width:	from 20 mm to 112 mm
Thickness label:	from 0.06 mm to 0.19 mm
Roll dimension:	127 mm OD (5.0" OD)
Fonts:	8 alphanumeric fonts fixed, one true type fonts with rotation at 0, 90, 180, and 270
Barcodes available:	code 39, code 39C, code 93, code 128uCC, Code 128 (subsets A, B, C) ??Codabar, Interleave 2 of 5, EAN-8, EAN-13, EAN-128, UPC-A, UPC-E, EAN and UPC 2 (5) digits add-on, MSI, Plessey, POSTNET, China Post, ITF-14, EAN14
2D barcodes available:	PDF-417, MAXICODE, DATA MATRIX, QR code
Memory:	2 MB DRAM, 2 MB Flash Memory
Interfaces:	RS 232 serial, parallel, USB 1.1
Dimensions:	240x200x164 mm
Power supply:	switching 100/240 VAC, 3.75A 24V DC (external adapter)
Operating temperature:	from 5° to 40° C
Standard connection cable:	length 1.5 m



SCIGATE AUTOMATION (S) PTE LTD

No.1 Bukit Batok Street 22 #01-01 Singapore 659592
Tel: (65) 6561 0488 Fax: (65) 6562 0588
Email: sales@scigate.com.sg Web: www.scigate.com.sg
Business Hours: Monday - Friday 8.30am - 6.15pm

