

## General information

PVS28020191003

The UWT 6008 Profibus DP weight transmitter is the result of many years of experience. It is a unique product in the weight transmitter family and is ideal for all industrial applications where it is necessary to know the load distribution on the different cells. The UWT 6008 Profibus DP weight transmitter is able to monitor all load cells and generate alarms due to excessive cell signal drift, missing connections, failure of one of the cells, unbalanced weight distribution. The emulative control allows the continuity of work of the weighing system even in case of failure on one of the load cells, up to the replacement of the same. The Software Optimization is given for free. This Software allows you to run certain activities such as calibration or monitoring directly from your computer. The Optimization software is provided by Pavone Systems and guarantees a perfect instrument run.



Software Optimization 1.3.12: [optimization\\_weighing\\_software.zip](#)

Profibus GSD file: [uwt\\_6008\\_profibus\\_gsd.zip](#)

Technical Manual: [uwt-6008\\_en.pdf](#)

All indicated data may be changed without notice.  
All the measures indicated are expressed in millimeters (mm).




**SCIGATE AUTOMATION (S) PTE LTD**  
 No.1 Bukit Batok Street 22 #01-01 Singapore 659592  
**Tel: (65) 6561 0488 Fax: (65) 6562 0588**  
**Email: sales@scigate.com.sg Web: www.scigate.com.sg**  
**Business Hours: Monday - Friday 8.30am - 6.15pm**



## Technical specifications

PVS28020191003

<b>Measuring range:</b>	-3.9 ÷ +3.9 mV/V
<b>Input sensitivity:</b>	0.02 µV/count
<b>Full scale non-Linearity:</b>	<0.01%
<b>Gain drift:</b>	< 0.001% FS/°C
<b>Display:</b>	128 x 64-pixel graphic LCD
<b>A/D Converter:</b>	24 bits
<b>Internal Resolution:</b>	> 16.000.000 points
<b>Transducer input voltage:</b>	5 Vdc (230 mA max.)
<b>Frequency signal acquisition:</b>	12.5 ÷ 300 Hz
<b>Visible resolution (in divisions):</b>	999999
<b>Divisions value (adjustable):</b>	x1, x2, x5, x10, x20, x50
<b>Decimal figures range:</b>	0 ÷ 4
<b>Temperature range:</b>	-10 ÷ + 50°C (humidity max 85% no condensation)
<b>Storage temperature:</b>	-20 ÷ +70°C
<b>Filter:</b>	5 ÷ 250 Hz
<b>Logic output:</b>	2 relays, Max. 48 Vac/Vdc, 2A each
<b>Logic input:</b>	2 opto-isolated at 12/24 Vdc PNP (external power supply)
<b>Serial port:</b>	1 USB device + 1 RS232C + 1 RS485
<b>Analog output Non-Linearity:</b>	< 0,02%
<b>Temperature drift analog output:</b>	0,001% FS / °C
<b>Power supply:</b>	12-24 Vdc ±15% - Power consumption 4 W
<b>Microcontroller:</b>	ARM Cortex M0+ at 32 bits, 256KB Flash reprogrammable on-board from USB
<b>Data storage:</b>	64 Kbytes expandable up to 1024 Kbytes
<b>Regulatory compliance:</b>	EN61000-6-2, EN61000-6-3 for EMC; EN61010-1 for Electrical Safety, EN45501 for metrology
<b>Number of load cells:</b>	1 ÷ 8
<b>Dimensions:</b>	100 x 75 x 110 mm (L x H x P)

All indicated data may be changed without notice.  
All the measures indicated are expressed in millimeters (mm).

# Weight Transmitter **UWT 6008 Profibus DP**



All indicated data may be changed without notice.  
All the measures indicated are expressed in millimeters (mm).