


Orbit[®] 3 EtherNet/IP[™] Interface



Description

The PIM, is a PLC compatible EtherNet/IP[™] to ORBIT[®]3 interface module, that enable easy connections between any EtherNet/IP[™] enabled controller and Solartron's flexible ORBIT[®]3 digital measurement system.

The PIM makes it simple to interface a wide range of contact and non contact linear measurement sensors, rotary encoders, temperature and pressure sensors and discrete inputs and outputs via EtherNet/IP[™]. This stand alone, Din Rail mounted module provides one EtherNet/IP[™] port and one ORBIT[®]3 port which can power up to ten sensors;. This can be extended up to a maximum of 150 sensors with the use of supplementary power modules.

The device uses an AnyBus Compact Com M40 module to communicate on the EtherNet/IP[™] network. This is a pre-certified device, as it uses standard operational settings from AnyBus, thus providing network conformance.

It should be noted that afore-mentioned network conformance applies to the EtherNet/IP[™] interface **only** and not to the complete product.

The EtherNet/IP[™] protocol driver supports the Explicit and Cyclic Messaging implementation of the protocol as a server. The EtherNet/IP[™] port is a very powerful data transfer tool designed for easy connection to Rockwell Automation PLCs. Applications are found in many industries including manufacturing, automation and control, power generation and food processing.

EtherNet/IP[™] is credited to ODVA

Precision. Quality. Reliability

www.solartronmetrology.com • sales.solartronmetrology@ametek.com

EtherNet/IP™

The EtherNet/IP™ protocol is one of the primary connectivity tools to different Rockwell platforms or any other PC's that support EtherNet/IP™. The Explicit Messaging aspect of the protocol has been implemented for reading and setting individual parameters, cyclic messaging has been implemented to facilitate synchronised readings

General Protocol Information

Messaging	Explicit and Cyclic Messaging Supported 125 word read and write data lengths
-----------	---

EtherNet/IP Server Specifications

In server mode, the module accepts commands from one or more clients to read/write data stored in the modules internal registers

Connections	4 cyclic, 6 explicit
CIP Services Supported	0x4C - CIP Data Table Read


Orbit® 3 Digital Measurement System

The Solartron Orbit® 3 Digital Measurement System, in conjunction with Solartron's wide range of transducers, provides a limitless set of measuring system solutions, with numerous different interfaces to computers and PLC's, making Orbit® 3 completely flexible. Compatible products include both Contact and Non-Contact linear measuring transducers (gauging probes), specialist transducers and third party transducer interfaces.

Orbit® 3 – The Total Measurement System from Solartron Metrology

FEATURES

- **Excellent metrology performance**, high **accuracy**, high resolution and excellent **repeatability**
- Excellent lifetime value – low maintenance costs due to the high reliability of mechanics and electronics
- Wide range of compatible transducers
- **Fast reading rates** with **high data integrity**
- Network up to 150 different transducers with one interface
- Communicate with any computer or PLC
- Range of Software drivers and tools for easy set up



Technical Specification

Performance	
	PIM EtherNet/IP Interface
Connection	EtherNet/IP
Data Rate (max) Baud	12 MB
No of Modules (Note 1)	150 using Explicit Messaging
	50 using Cyclic Messaging
No of Module powered Readings per second	10 direct, up to 150 with additional Power Supply modules
	400 readings/sensor/sec for 2 sensors
	150 readings/sensor/sec for 24 sensors
Power Supply	24 VDC nominal (18V to 32 VDC allowed).
	PIM provides power for up to 10 Orbit Probe and up to 4 LTH/LTM Laser modules
Indications	Integral LCD Screen and Keypad for screen selection
Configuration PC Port	micro USB port
Ethernet Port	2 x RJ485 Connectors

Environment

Sealing	IP43
Operating Temperature °C	-20 to +70
Storage Temperature °C	0 to 60
EMC Emissions	EN61000-6-3
EMC Immunity	EN61000-6-2

Note 1: Explicit messaging can read the following items: measurement, status, max and min, from 150 sensors. Cyclic messaging can read measurement and status synchronised from 50 sensors

Configuration and Set Up

The PIM Orbit network is easily configured using a PC based application that utilises the PIM's Micro USB interface. Once configured the Orbit Network is remembered and no further setting up is required unless additional transducers are required.

The configuration application is also used to set EtherNet/IP™ settings such as DHCP enable, host name, IP address, subnet mask and default gateway.


Accessories

+24V Power Block with Mains leads. Available with UK, EU and US plugs

Spare T-con Mounts

Spare Earthing/Mounting brackets

Dimensions



For 3D drawings, please contact sales.solartronmetrology@ametek.co.uk

United Kingdom - Head Office

Solartron Metrology
Steyning Way
Bognor Regis
West Sussex
PO22 9ST
Tel: +44 (0) 1243 833333
Fax: +44 (0) 1243 833322
Sales.solartronmetrology@ametek.com

France

Solartron Metrology
Rond-point de l'Espine des Champs
Buroplus - Bat. D
Elancourt 78990
Tel: +33 (0)1 30 68 89 50
Fax: +33 (0)1 30 68 89 59
france.solartronmetrology@ametek.com

Germany

Ametek GmbH
Solartron Metrology Division
Rudolf-Diesel-Strasse 16
40670 Meerbusch
Tel: +49 (0) 2159 9136 500
Fax: +49 (0) 2159 9136 505
vertrieb.solartron@ametek.de

Brazil

Ametek do Brasil, Ltda
Rod. Eng Ermenio de Oliveira Penteado, Km 57, SP75
Bairro Tombadouro
13337-300, Indaiatuba, SP, Brazil
Tel: +55 19 2107 4126

India

Ametek Instruments India Private Limited
1st Floor, Left Wing
Prestige Featherlite Tech Park
Plot #148, EPIP II Phase
Whitefield, Bengaluru 560 066
Karnataka, India
Tel: +91 80 6782 3200
Fax: +91 80 6782 3232

USA

Solartron Metrology
USA Central Sales Office
915 N. New Hope Road, Suite C
Gastonia, NC 28054
Tel: +1 800 873 5838
Fax: +1 704 868 8466
usasales.solartronmetrology@ametek.com

China

AMETEK Commercial Enterprise (Shanghai) Co. Ltd
No. 155 Puhui Road
Ju Ting Economic Development Zone
Shanghai 200131, China
Tel: +86 21 5763 2509
Fax: +86 21 5866 0969 Ext. 261/262
china.solartronmetrology@ametek.com



**Solartron
Metrology**

Precision Driven

Offices worldwide
Agent and distributor details
available at
www.solartronmetrology.com



Q09540

Solartron pursues a policy of continuous development. Specifications in this document may therefore be changed without notice.



SCIGATE AUTOMATION (S) PTE LTD

No.1 Bukit Batok Street 22 #01-01 Singapore 659592

Tel: (65) 6561 0488

Fax: (65) 6562 0588

Email: sales@scigate.com.sg

Web: www.scigate.com.sg

Business Hours: Monday - Friday 8.30am - 6.15pm

AMETEK®
ULTRA PRECISION TECHNOLOGIES

Precision. Quality. Reliability

www.solartronmetrology.com • sales.solartronmetrology@ametek.com