

## 1U Console Drawer


1U Console LCD Drawer or Switch can save space, power and money. It only takes 1U (1.75in), same height as the rack space. It is an ideal solution for ASP, ISP, telecommunication companies, and testing rooms.

\*All specifications are subject to change without notice.



### What is KVM?

KVM is the acronym for keyboard, Video, Mouse. More specifically, multiple computers are connected to the KVM and controlled from a single set of keyboard, monitor and mouse. Although there are multiple computers connected the KVM, however only one can be controlled at a time. Control of each computer is done separately via the use of switches on the KVM. It does this by fooling each computer into thinking that it is currently actively connected to a separate keyboard, mouse and monitor. Since the KVM incorporates only a single set of keyboard, monitor and mouse, it saves space, cuts cost as well as increase the efficiency of work done. Along with the ease of control, it saves time and adds valuable flexibility to the whole system.



## 19" LDS410D-16P



### Specifications


Display Area(mm)	376.3(H)x301.1(V)
Pixel Pitch	0.294(H)x0.294(V)
Number of Pixels	1280(H)x1024(V)
Contrast Ratio	500:1
Display Color	16.7M
Brightness(CD/m <sup>2</sup> )	250(typ.)
Viewing Angle	-85~85(H);-85~85(V)
I/O	Power:12V DC in with AC adapter Keyboard:USB Mouse:USB VGA: 15-pin D-Sub
Keyboard and Key Pad	88-Key keyboard and integrated Touch Pad 17-Key numerical key pad
Power Consumption	35 Watts
Power Supply	AC 100-240V Universal
On-Screen Display	Contrast, Brightness, H/V Position, H/V Size H-scaling,Auto-adjust,Color Temp.(9300,6500, User),Red-Gain,Blue-Gain,Green-Gain,Gamma, Recall,Phase,OSD & Exit
Hot Key Control	OSD Hot Key
Environmental Consideration	Operating temperature:0°C~50°C (32F~122F) Storage temperature:-20°C~60°C (-4F~140F)
Humidity	10~85% in operating;10-90% in storage
Size	609mm(D) x482mm(W) x44mm(H)

# 1U Console Drawer

## 1U Console Drawer

Mechanical Drawing

MODEL NAME:LDS410D-16P



\* Note: this is a simplified drawing and some components are not marked in detail. Please contact our sales representative if you need further product information.

### Order Information

		19"
KVM	16 Port	LDS410D-16P

\* Note: Please contact our sales representative for detail information.



**SCIGATE AUTOMATION (S) PTE LTD**

No.1 Bukit Batok Street 22 #01-01 Singapore 659592  
 Tel: (65) 6561 0488 Fax: (65) 6562 0588  
 Email: sales@scigate.com.sg Web: www.scigate.com.sg

Business Hours: Monday - Friday 8.30am - 6.15pm