

15" Fanless Full IP67 Panel PC (Intel® Atom™ D2550 Platform)

MODEL #: R15ID3S-67C3

Mechanical Design



Features:


- Intel® Atom™ Dual Core D2550 1.86GHz Processor
- Fanless Design
- Full IP67 dust/water resistant
- Stainless Housing with Anti-Corrosion Treatment
- Optical Bonding with Anti-moisture Treatment
- 5 Wire Resistive Touch/ Anti-Reflection Protection Glass (Optional)

brushed stainless

IP67 connector / cable



2 x USB LAN COM2 Power



* Note: this is a simplified drawing and some components are not marked in detail. Please contact our sales representative if you need further product information.

System Specifications

TFT Characteristics

- Size/Type : 15" TFT
- Resolutions : 1024x 768
- Brightness : 250 cd/m² (typ.)
- Contrast Ratio : 700 : 1 (typ.)
- Viewing Angle : -70~70(H); -65~60(V)
- Max. Colors : 16.2M

Dimension

- Dimension : 64.4 x 457.4 x 370 mm (WxLxH)
- Weight : 8.35 kg

SBC Specifications

- Processor : Intel® Atom™ Dual Core D2550 1.86GHz Processor
- BIOS : AMI UEFI BIOS
- System Chipset : NM10
- System Memory : DDR3 Default 2GB, Max. 4GB
- Graphic Chipset : Integrated Graphic
- Ethernet : 1000 Base-Tx Gigabit Ethernet Compatible
- Audio : Realtek ALC655 codec
- USB : 2 x USB 2.0
- Serial : 1 x RS232
- Storage : 32GB mSATA SSD (Default)
- Expansion Slot : 1 x Mini PCIe for Wifi or 3G (Option)
- Power Input : 12V DC-IN

* A customized housing is needed if you would like to have the PCI expansion.

Power Specifications

- Power Input : 12V DC IN (Lockable Power Jack)
- Power Consumption : 45W (typ.) (Max. backlight & high CPU load)

Accessories

- External Power Supply 80W w/power cord

Environment Considerations

- Operating Temperature : 0 deg.C to 45 deg.C
- Operating Humidity : 30% to 90% (non condensing)

Input/ Output Connectors

- Ethernet LAN : 1 X RJ45-10/100/1000 Mbps
- COM : 1 X RS232
- USB : 2 x USB
- Power : 1 X 12VDC

Order Options

SBC	PANEL PC
RAM : SODIMM DDR3 1GB/2GB/4GB	Mechanical : Stainless Chassis
Storage : 2.5" HDD/ Mini Pcle SSD	Touch : 5 Wires Resistive(Optional)
	OS : Windows 7 embedded / Windows XP embedded (Optional)




15" Fanless Full IP67 Panel PC (Intel® Atom™ D2550 Platform)

MODEL #: R15ID3S-67C3



Pin Assignment of cables

Power Cable





Pin No.	Symbols	Color
CN1-3	GND	Black
CN1-2	shield	
CN1-1	VCC	White

LAN Cable



Plug	Wire Color	Conn.	
1	Orange / White	1	Twist
2	Orange	2	
3	Green / White	3	Twist
4	Blue	4	
5	Blue / White	5	Twist
6	Green	6	
7	Brown / White	7	Twist
8	Brown	8	



Serial Cable



Pin No.	Symbols	Color
CN1-1	DCD-CON2	Green
CN1-2	DSR-CON2	Brown
CN1-3	RXD-CON2	Red
CN1-4	RTS-CON2	Orange
CN1-5	TXD-CON2	Blue
CN1-6	CTS-CON2	White
CN1-7	DTR-CON2	Purple
CN1-8	RI-CON2	Yellow
CN1-9	GND-CON2	Black
CN1-10	NC	

Pin No.	Symbols	Color
CN2-1	DCD-CON2	Green
CN2-6	DSR-CON2	Brown
CN2-2	RXD-CON2	Red
CN2-7	RTS-CON2	Orange
CN2-3	TXD-CON2	Blue
CN2-8	CTS-CON2	White
CN2-4	DTR-CON2	Purple
CN2-9	RI-CON2	Yellow
CN2-5	GND-CON2	Black
CN2-10	NC	

USB Cable



Pin No.	Symbols	Color
CN1-1	VCC	RED
CN1-2	VCC	RED
CN1-3	D-	WHITE
CN1-4	D-	WHITE
CN1-5	D+	GREEN
CN1-6	D+	GREEN
CN1-7	GND	BLACK
CN1-8	GND	BLACK
CN1-9	Braid	

Pin No.	Symbols	Color
CN2-1	VCC	RED
CN3-1	VCC	RED
CN2-2	D-	WHITE
CN3-2	D-	WHITE
CN2-3	D+	GREEN
CN3-3	D+	GREEN
CN2-4	GND	BLACK
CN3-4	GND	BLACK
Braid connect to the housing		

twisted pair

twisted pair



SCIGATE AUTOMATION (S) PTE LTD

No.1 Bukit Batok Street 22 #01-01 Singapore 659592

Tel: (65) 6561 0488

Fax: (65) 6562 0588

Email: sales@scigate.com.sg

Web: www.scigate.com.sg

Business Hours: Monday - Friday 8.30am - 6.15pm