

R17ID7T-PMM1PS 17" Panel PC (Intel® Atom Dual Core D2550)

Mechanical Design



Panel Mount (8 mm front bezel)



PCI Input

106.68 mm



175.26 mm

Feature :


- Designed for one PCI Slot
- No convex part on IO side edge
- Only Support half-size PCI Card
15.24 x 175.26 x 106.68 mm



SCIGATE AUTOMATION (S) PTE LTD

No.1 Bukit Batok Street 22 #01-01 Singapore 659592
Tel: (65) 6561 0488 Fax: (65) 6562 0588
Email: sales@scigate.com.sg Web: www.scigate.com.sg
Business Hours: Monday - Friday 8.30am - 6.15pm

Fully Integrated I/O





1. PCI Card Slot
2. Audio Jack
3. RS-232 Conn.(Optional)
4. USB
5. RJ-45
6. VGA Out
7. RS-232 Conn.
8. PS/2
9. Power Reset Button
10. Power On Button
11. 12V DC-in Terminal Block (Phoenix type)


Mechanical design :



SIDE VIEW



CUT OUT



BOTTOM VIEW

- * Total Dimension (L x H x D) : 440 x 360 x 93 mm
- * Cutout dimension (L x H) : 411 x 330 mm
- * Measurements shown in mm
- * Tolerance of all dimensions is shown as follow 0~30 mm ± 0.1 mm, 30~50 mm ± 0.15 mm, 50~120 mm ± 0.2 mm, above 120 mm ± 0.25 mm
- * Note: this is a simplified drawing and some components are not marked in detail. Please contact our sales representative if you need further product information.

Specifications

System :

- CPU : Intel®Atom Dual Core D2550 1.86 GHz
- Memory : 1 x SODIMM Max 4GB DDR3L 800/1066
- System Chipset : Intel® NM10
- SATA : 2 x SATA II
- LAN : Dual Broadcom BCM 57780 GbE controller
- Audio Codec : Realtek ACC886 HD Audio Codec

Input / Output :

- Serial Ports : 2 x RS232, 1 x RS232/422/485
- USB Ports : 4 x USB
- Keyboard / Mouse : 2 x PS/2
- Ethernet : 2 x RJ 45-10/100/1000 Mbps
- VGA : 1 x VGA (female)
- Audio : Line-Out, Line-In, Mic in

●Default setting:RS232

Expansion Slot :

- 1 x PCI (15.24 x 175.26 x 106.68 mm)
* A customized housing is needed if you would like to have the PCI expansion.

Power Specifications :

- Power Input : Terminal block Phoenix type / 12V DC-in
- Power Consumption : 60W (typ.)(Max. backlight & high CPU load)

Accessories :

- External Adapter : 110~230V Ac-in power adapter

Panel Spec :

- Size/Type : 17" TFT
- Resolutions : 1280 x 1024
- Brightness : 350 cd/m² (typ.)
- Contrast Ratio : 800 : 1(typ.)
- Viewing Angles : -85~85(H);-80~80(V)
- Max Colors : 16.7M(6bits+FRC)

Environment Considerations :

- Operating Temperature : 0 deg.C to 45 deg.C
- Operating Humidity : 30% to 90% (non condensing)

OS BSP / Driver Support :

- Support Windows 7 / Windows XP Embedded / Windows XPP Embedded / Linux3.2.0

Order Options :

- Mechanical : Open frame
- Touch : Resistive

- Storage : 2.5" HDD/ 2.5" SSD
- RAM : DDR3L 800/1066 Max 4GB
- OS : Windows XPE(Optional)
Windows XPPE (Optional)
Windows 7 (Optional)
Linux(Optional)

(A customized housing is needed if you have demands of SAW/IR/SC touch)

