


# R19ID7T-PMA1 19" Panel PC (Intel® Atom Dual Core D2550+NM10 Platform)


## Mechanical Design



Panel Mount (8 mm front bezel)



Mechanical design  
Dimensions



- |                            |                                |
|----------------------------|--------------------------------|
| 1. RS-232 Conn. (Optional) | 7. RS-232 Conn.                |
| 2. Audio                   | 8. PS/2                        |
| 3. DVI(Optional)           | 9. 12V DC-IN                   |
| 4. LAN                     | 10. Brightness Adjustment Knob |
| 5. USB                     | 11. Power On Button            |
| 6. VGA                     | 12. Power Reset Button         |


Fully Integrated I/O

FRONT VIEW




SIDE VIEW

BACK VIEW

IP65 CUT OUT



BOTTOM VIEW



- \* Measurements shown in mm
- \* Tolerance of all dimensions is shown as follow 0~30 mm ± 0.1 mm, 30~50 mm ± 0.15 mm, 50~120 mm ± 0.2 mm, above 120 mm ± 0.25 mm
- \* Note: this is a simplified drawing and some components are not marked in detail. Please contact our sales representative if you need further product information.

## Specifications

### System :

- CPU : Intel® Atom Dual Core D2550 1.86GHz Processor
- Memory Slot : DDR3 1600 MHz SO-DIMM Slot, Max. 4GB
- System Chipset : Intel® NM10
- Storage : 2 x SATA II
- LAN : Dual Broadcom BCM57780 GbE controller
- Audio Codec : Realtek ALC886 HD Audio Codec

### Input / Output :

- Serial Ports : 2 x RS232, 1 x RS232/422/485
  - USB Ports : 4 x USB Type-A Receptacle
  - Keyboard / Mouse : 2 x PS/2
  - Ethernet : 2 x RJ45-10/100/1000 Mbps
  - VGA : 1 x VGA (female)
  - Audio : Line-out, Line-in, Mic in
- Default setting:RS232

### Expansion Slot : (internal)

- 2 x Mini PCIe (1 for WiFi, 1 for 3G Module), 1 x PCI
- \* A customized housing is needed if you would like to have the PCI expansion.

### Power Specifications :

- Power Input : 12V DC IN
- Power Consumption : 57W (typ.)(Max.backlight & high CPU load)

### Accessories :

- External Adapter : 110~240V Ac-in 12V DC-output Power Adapter

### Panel Spec :

- Size/Type : 19"TFT
- Resolutions : 1280 x 1024
- Brightness : 400 cd/m<sup>2</sup>(typ.)
- Contrast Ratio : 1000 : 1(typ.)
- Viewing Angle : -85~85(H);-80~80(V)
- Max. Colors : 16.7M (8 bits/colors)

### Environment Considerations :

- Operating Temperature : 0 deg.C to 50 deg.C
- Operating Humidity : 30% to 90% (non condensing)

### OS BSP / Driver Support :

- Support Windows 7 embedded / Windows XP embedded

### Order Options :

- |  |  |
|--|--|
| Mechanical : Panel Mount (8 mm bezel)                                      | Storage : 2.5" HDD/ mSATA SSD                                    |
| Touch : 5-Wires Resistive or AR Protective Glass either one                | RAM : DDR3 1600 Max 4GB  |
| (A customized housing is needed if you have demands of SAW/IR/IT/SC touch) | OS : Windows 7 embedded Standard / Windows XP embedded(Optional) |



SCIGATE AUTOMATION (S) PTE LTD

No.1 Bukit Batok Street 22 #01-01 Singapore 659592  
 Tel: (65) 6561 0488 Fax: (65) 6562 0588  
 Email: sales@scigate.com.sg Web: www.scigate.com.sg

Business Hours: Monday - Friday 8.30am - 6.15pm



Note: All Specifications are subject to change without prior notice!

03-Jun-2016 V1.5