


Rugged Panel PC



Model:W12IB3S-VMM9

Product Features:

- Ultra Low Bay Trail N2930 1.83GHz Processor Fanless Design
- 4 Wire resistive touch screen
- -10 ~ +55°C Wide Range Operating Temperature
- Anti-Corrosion housing with Fanless Design
- 9V ~ 36V DC Isolation Wide Range Power (default)
- Anti-Shock & Vibration compliant with MIL-STD-810F/G
- Optional 6-60V DC Input, and Optional for Ignition On/Off delay
- Panel Mount for request
- Design to meet EN50155




Product Specifications:

SCIGATE AUTOMATION (S) PTE LTD
 No.1 Bukit Batok Street 22 #01-01 Singapore 659592
 Tel: (65) 6561 0488 Fax: (65) 6562 0588
 Email: sales@scigate.com.sg Web: www.scigate.com.sg
 Business Hours: Monday - Friday 8.30am - 6.15pm


Display	Model Name	W12IB3S-VMM9
	Size	12.1"
	Resolution (pixels)	1280 x 800
	Number of Colors	262.144 (6bits/color)
	Brightness (cd/m2)	400
	Contrast Ratio	1000 :1
	Viewing Angle	-88~88 (H) ; -88~88 (V)
	Active Area	261.12 (H) x 163.2 (V)
	Touch (optional)	4 wire resistive
	System	Processor
Chipset		Bay Trail SoC Chipset
BIOS		AMI 16Mbit Flash
Memory		1xDDR3L 1600 / 1333 MHz SO-DIMM, default 4GB, Max. 8GB
Ethernet		Intel® I210-AT GbE LAN
Storage		mSATA SSD, default 64GB
Input/Output	1 x USB 3.0, 1 x USB 2.0	
	1 x HDMI	
	1 x RS-232	
	1 x RS-232/422/485	
	1 x DC-IN Terminal Block	
	1 x WLAN or 3G Antenna in top (optional)	
Environment	Operating Temperature	-10 ~55°C
	Storage Temperature	-30 ~70°C
	Humidity	10 ~ 95% non-condensing
	Shock	MIL-STD-810F/G
	Vibration	MIL-STD-810F/G
	Power Input	9~36V DC in with isolation (Phoenix type) Optional 6-60V DC in, with Ignition On/Off delay
Driver OS Support	Safety	MIL-STD-810F/G
	Windows Embedded Standard 7 (64-bit)	
	Windows Embedded 8.1 Industry Pro 64-bit	
	Windows 10 IoT Enterprise	
Mechanical	Dimension(W x H x D)	310 x 215 x 52.7 mm
	Approximate Weight	2.8 kg*
Packing List	*Weight of this device will be more or less depending upon actual component configuration (IB32) SBC Manual & Driver CD	
Security Support	Trusted Platform Module (TPM 1.2)	

I / O View:



1. RS232
2. RS232/422/485
3. 1xUSB 2.0, 1xUSB 3.0
4. HDMI
5. 2xRJ45
6. Terminal Block 9~36V

Rear OSD Control Function:



Drawing w/o Mounting bracket:

