



# W22IH7T-PMA3 21.5" Panel PC (Intel® 4th Generation Core™ i5 Platform)



1. RS-232 (Optional)
2. Audio Jack
3. DVI (Optional)
4. USB
5. LAN
6. VGA
7. RS-232/422/485
8. RS-232
9. PS/2
10. 12V DC-in
11. Brightness Adjustment Knob
12. Power On Button
13. Power Reset Button

## Panel Mount (6 mm front bezel)

## Mechanical design

## Fully Integrated I/O

## Dimensions







### SIDE VIEW

### TOP VIEW

### SIDE VIEW

### BACK VIEW

### IP65 CUT OUT



### BOTTOM VIEW

- \* Measurements shown in mm
- \* Tolerance of all dimensions is shown as follow 0~30 mm ± 0.1mm, 30~50 mm ± 0.15 mm, 50~120 mm ± 0.2 mm, above 120 mm ± 0.25 mm
- \* Note: this is a simplified drawing and some components are not marked in detail. Please contact our sales representative if you need further product information.

## Specifications

### System :

- CPU : Intel 4th<sup>®</sup> Generation Core™ i5-4200M 2.5GHz (Max. 3.1GHz) Processor
- Memory Slot : 2 x SO-DIMM, Max 16GB DDR3L 1333/1600
- System Chipset : Intel<sup>®</sup> QM87 Chipset
- IDE/SATA : 2XSATA III
- LAN : Intel<sup>®</sup> Ethernet Controller I211-AT + Intel<sup>®</sup> Gigabit Ethernet PHY I218-LM
- Audio Codec : Realtek ALC888 HD Audio Codec

### Panel Spec :

- Size/Type : 21.5" TFT
- Resolutions : 1920 x 1080
- Brightness(cd/m<sup>2</sup>) : 250 (typ.)
- Contrast Ratio : 1000 : 1 (typ.)
- Viewing Angle : -89~89 (H) ; -89~89 (V)
- Max. Colors : 16.7M

### Input / Output :

- Serial Ports : 2 x RS232, 1 x RS232/422/485
  - USB Ports : 4 x USB 3.0
  - Keyboard / Mouse : 2 x PS/2
  - Ethernet : 2 x RJ 45-10/100/1000 Mbps
  - VGA : 1 x VGA (female)
  - Audio : Line-Out, Line-In, Mic in
- Default setting: RS232

### Expansion Slot :

- 2 x Mini PCIe (1 for WiFi, 1 for 3G Module), 1 x PCI
- \* A customized housing is needed if you would like to have the PCI expansion.

### Power Specifications :

- Power Input : 12V DC IN
- Power Consumption : 78W (typ.)(Max.backlight & high CPU load)

### Accessories :

- External Adapter : 110~240V Ac-in Power Adapter

### Environment Considerations :

- Operating Temperature : 0°C to 50°C
- Operating Humidity : 30% to 90% (non condensing)

### OS BSP / Driver Support :

- Support Windows 7 / Windows 8 Embedded / Windows 10 IoT Enterprise

### Order Options :

- |                                      |                                |
|--------------------------------------|--------------------------------|
| Mechanical : Panel Mount(6 mm bezel) | Storage : 3.5" HDD/ 2.5"SSD    |
| Touch : 5 Wires Resistive(Optional)  | RAM : DDR3L 1333/1600 MAX 16GB |

(A customized housing is needed if you have demands of SAW/IR/SC touch)



## SCIGATE AUTOMATION (S) PTE LTD

No.1 Bukit Batok Street 22 #01-01 Singapore 659592  
 Tel: (65) 6561 0488 Fax: (65) 6562 0588  
 Email: sales@scigate.com.sg Web: www.scigate.com.sg



Note: All Specifications are subject to change without prior notice!

Business Hours: Monday - Friday 8.30am - 6.15pm

02-Aug-2016 V1.6