



24" Flat P-CAP Marine Display


Model#: W24L100-MRA1FP

Features :

- 24" 1920 x 1080 resolution with projective capacitive multi-touch screen
- Edge-to-edge narrow bezel design and fanless cooling system
- Color calibrated for ECDIS compliance (Optional)
- Capacitive touch keys for quick function access and display control (Support ECDIS DAY, DUSK, and NIGHT mode switching)
- Meet the requirements of Industrial marine standards, including IEC60945 4th Edition, DNVGL-CG-0339, IACS E10



1. USB (touchscreen)
2. RS232 (remote control)
3. HDMI 1.4
4. DVI-D
5. VGA
6. DC input



* Note: this is a simplified drawing and some components are not marked in detail. *Please contact our sales representative if you need further product information.

Display Specifications

Resolution	: 1920 x 1080
Pixel Pitch	: 0.276 (H) x 0.276 (V) mm
Contrast Ratio	: 5000:1 (typ.)
Brightness	: 350 cd/m ² (typ.)
Viewable Angle	: 89°/89°/89°/89° (typ.) (Up/Down/Left/Right)
Active Display Area	: 531.36 (H) x 298.89 (V) mm
Max Colors	: 16.7 M colors, 8 bits/color
Touch Screen	: Projective Capacitive Multi-touch (Optional AR Protection Glass)
Buzzer	: 75 dB~80 dB, 2300 Hz, 1m

Input / Output Connectors

DVI input	: DVI-D 24pin (female)
HDMI input	: 1 x HDMI 1.4
VGA input	: D-SUB 15pin (female)
Remote control via RS232	: D-SUB 9pin (female)
Touch	: USB type A (female)
DC input	: Terminal block 3pin (phoenix type)

Power Specifications

Power Input	: *24V DC-in with Isolation (9~36V acceptable)
-------------	------------------------------------------------

User Controls:

OSD control via programmable capacitive touch keys (ECDIS, Home, Brightness(+,-), Power)
Remote control via RS232 serial interface

Mechanical

Mechanical Mounting	: Panel Mount, VESA Mount
Dimension	: 595mm x 385mm x 63.8mm
Panel Mount Cutout	: 572mm x 363mm
Housing	: Anodized Aluminum Bezel
IP Rating	: IP66 (Front Side)

Environmental

Operating Temperature	: -15 to 55 deg.C
Operating Humidity	: 5% to 95% (non condensing)
Anti-Vibration	: 0.7g@DNVGL CG-0339 (Class A)
Anti-Shock	: 15G, 11ms duration

Certification

DNVGL-CG-0339, IEC60945 4th, IACS E10, CE, FCC



SCIGATE AUTOMATION (S) PTE LTD

No. 1 Bukit Batok Street 22 #01-01 Singapore 659592
Tel: (65) 6561 0488 Fax: (65) 6562 0588
Email: sales@scigate.com.sg Web: www.scigate.com.sg
Business Hours: Monday - Friday 8.30am - 6.15pm

*Only 24V DC have approval by DNVGL certificate

Note: All Specifications are subject to change without prior notice!

ed date: 27-Dec-2017 V1.7