

Panel Mount LCD



SCIGATE AUTOMATION (S) PTE LTD

No.1 Bukit Batok Street 22 #01-01 Singapore 659592
 Tel: (65) 6561 0488 Fax: (65) 6562 0588
 Email: sales@scigate.com.sg Web: www.scigate.com.sg
 Business Hours: Monday - Friday 8.30am - 6.15pm


Panel Mount LCD



23.8"(16:9) Specifications




| | |
|--------------------------------|---|
| Model Name | W24L100-PMA2 |
| Panel Size | 23.8" |
| Active Display Area(mm) | 527.04 (H) x 296.46 (V) |
| Resolution | 1920 x 1080 |
| Brightness(cd/m ²) | 250 (Typical) |
| Contrast Ratio | 3000:1 (Typical) |
| Viewing Angles(CR>=10 L/R/U/D) | -89~89(H) ; -89~89(V) |
| Display Colors | 16.7M (8 bits/color) |
| Standard Input Signal | 1 x VGA (D-sub 15) 1 x HDMI (Type-A) |
| Touch Screen(Optional-1) | Resistive Touch Protective Glass |
| Touch Screen(Optional-2)* | SAW Touch (Surface Acoustic Wave) |
| Touch Interface | USB / RS232 |
| Audio / Speakers (Optional)* | Audio line in (3.5mm) + Speaker x2 |
| OSD | 5 Keys: -, +, Power, Esc, Enter |
| Power Input | 12V DC input (2.5ψ) with external AC-DC Adapter (100V~240V) |
| Power Consumption | 40W typical, Normal operation |
| Operating temperature | 0~50°C |
| Storage Temperature | -10~60°C |
| Accessories | Power AC-DC Adapter(100V~240V) VGA cable (1.8m) HDMI cable (2m) |



| I/O Optional | |
|--------------|---|
| Optional 1* | 1 x VGA (D-sub 15) 1 x HDMI (Type-A) 1 x DVI-D |
| Optional 2* | 1 x VGA (D-sub 15) 1 x DVI-D 1 x S-Video 1 x Composite |

*Outside dimension and I/O will be different from standard

Mechanical Drawing (without touch)



* Note: The mechanical drawing may change when adding touch screen. Please contact our sales representative if you need further product information.