	DRIES	SHUNT CAL / RCAL RESISTORS
Drawing Number: FI1208-A		
POWER RATING	G MATERIAL	
1/4 WATT	PRECISION METAL FILM	
TOLERANCE	TEMPERATURE COEFFICIENT	
0.01 %	10 PPM	

SHUNT CAL VALUE	BRIDGE RESISTANCE	SHUNTED OUTPUT
43.575K OHMS	350 OHMS	2.00 mV/V
60.4K OHMS	350 OHMS	1.44 mV/V
87.325K OHMS	700 OHMS	2.00 mV/V
	350 OHMS	0.87 mV/V
100K OHMS	700 OHMS	1.74 mV/V
	1000 OHMS	2.49 mV/V
150K OHMS	700 OHMS	1.16 mV/V
	1000 OHMS	1.66 mV/V
174.825K OHMS	350 OHMS	0.50 mV/V
200K OHME	700 OHMS	0.87 mV/V
	1000 OHMS	1.25 mV/V
301K OHMS	1000 OHMS	0.83 mV/V
	43.575K OHMS 60.4K OHMS 87.325K OHMS 100K OHMS 150K OHMS 174.825K OHMS 200K OHMS	43.575K OHMS 350 OHMS 60.4K OHMS 350 OHMS 87.325K OHMS 700 OHMS 100K OHMS 350 OHMS 100K OHMS 700 OHMS 100K OHMS 700 OHMS 1000 OHMS 1000 OHMS 150K OHMS 1000 OHMS 174.825K OHMS 350 OHMS 200K OHMS 1000 OHMS

