



FEATURES

- Uni-directional/Bi-directional Output, Differential Input
- 4-20 mA Output
- Bridge Excitation: 5 or 10 VDC (DIP Switch)
- Ranges: 0.5, 1.0, 1.5, 2.0, 2.5, 3.0, 4.0, 10.0 mV/V (DIP Switch)
- 256 Selectable Shunt Combinations: 30k Ω , 43.7k Ω , 60.4k Ω , 87.6k Ω , 100k Ω , 150k Ω , 300k Ω , 432k Ω (DIP Switch)
- Externally Accessible Shunt Cal Activation Button
- Digitally Controlled Remote Shunt
- Internal Span and Offset Potentiometers
- Sensor Polarity Reversal DIP Switch
- Zero Shift DIP Switch
- Class 1 Certification for Aerospace and Medical Grade Devices

IMPORTANT NOTE: DO NOT CONNECT DEVICE TO POWER SUPPLY WHEN POWER SUPPLY IS ALREADY ON



SPECIFICATIONS

PARAMETER	MIN.	TYP.	MAX.	UNIT
Power Supply	12.5		26	VDC
Current Consumption		30 ¹	100	mA
Load Impedance			500	Ohm
Sensor Impedance	350/75 ⁴		5000	Ohm
Bandwidth (Setting 1)		1000		Hz
Bandwidth (Setting 2)		10000 ²		Hz
Bandwidth (Setting 3)		25000 ³		Hz
Common Mode Rejection Ratio	120			dB
Noise		15		μ A _{p-p}
Output Span range	-10		10	% of FSR
Output Zero range	-10		10	% of FSR
Gain Drift with Temperature	-25		25	PPM of FSR
Nonlinearity	0.01		0.01	% of FSR
Zero Drift with Temperature	-25		25	PPM of FSR
Operating Temperature	32 [0]		158 [70]	°F [°C]
Storage Temperature	-40 [-40]		185 [85]	°F [°C]
Relative Humidity		95% at 100 [39]		°F [°C]

PHYSICAL FEATURES

Material	Stainless steel cover with aluminum body fastened by magnets
Protection	IP50
Weight (approx.)	0.23 lb (104 g)
Power	LED Indicated

CONFORMITY

RoHS	2011/65/EU
CE	EN61326-1:2013; EN55011:2009 (Amended by A1:2010) Class 1 Certification for Aerospace and Medical Grade Devices


¹ Stand-alone current consumption. Adding the strain gauge and output current will increase current consumption

² Only for Sensitivity of 1.0 mV/V or Greater


³ Only for Sensitivity of 1.5 mV/V or Greater

⁴ 350 Ohms for 5 V excitation and 75 Ohms for 10 V excitation

DIMENSIONS inches [mm]



DIP SWITCHES CONFIGURATION



SENSOR SIDE

PIN # WIRING CODE


1	+ EXCITATION
2	+ SIGNAL
3	- SIGNAL
4	- EXCITATION/SHIELD ⁴

⁴ For 6 wire sensors, connect +SENSE to +EXCITATION and -SENSE to -EXCITATION.

Note: Sensor cable shield connections should be grounded on one end, either the sensor side or the IAA sensor input side, to avoid potential ground loops.




SCIGATE AUTOMATION (S) PTE LTD
No. 1 Bukit Batok Street 22 #01-01 Singapore 659592
Tel: (65) 6561 0488 Fax: (65) 6562 0588
Email: sales@scigate.com.sg Web: www.scigate.com.sg
Business Hours: Monday - Friday 8.30am - 6.15pm



POWER SIDE

PIN	WIRING CODE		COLOR
1	+Vin	Power Supply	Red
2	Gnd	Power Ground/Shield	Black
3	Shunt	Remote Connection	Orange
4	Gnd	Output Ground/Shield	Blue
5	Vout/Iout	Output Signal	Green



Power is 12.5VDC to 26VDC.

Note: All grounds are connected together and pass through. Power and instrument cable shield connections should be grounded on one end, either at the power and instrument side, or the IAA side, to avoid potential ground loops.

Drawing Number: FI1364-G

FUTEK reserves the right to modify its design and specifications without notice. Please visit <http://www.futek.com/salesterms> for complete terms and conditions.

10 Thomas, Irvine, CA 92618 USA

Tel: (949) 465-0900

Fax: (949) 465-0905

www.futek.com



RoHS



U.S. Manufacturer