

FUTEK MODEL IHH300 (D531)

STOCK NUMBER: SEE BELOW

HAND HELD PORTABLE DIGITAL DISPLAY

FOR USE W/ ANY STRAIN GAGED SENSOR


(PREVIOUSLY D530 SERIES)

Drawing Number: FI1022

INCH [mm]

FEATURES:

- 8000 Samples per second
- Maximum reading 9999 with floating decimal point
- Input range 1-4 mV/V
- Powered by 9 volt rechargeable battery (supplied)
- Battery life of up to 20 hrs (Depending on use and battery condition)
- Supplied with charging adapter (110V input)
- 5 Selectable filter settings 170, 250, 500, 1500, 3600 Hz
- RS232C (Printer Output), Supplied with cable and connector (4800 Baud, No parity, 8 Data, 1 Stop Bit)
- Operation Modes- Track, Peak/Valley, First Peak/Valley Hold
- Display can store 15 different custom sensor calibrations
- Stores up to 1000 Data points
- Includes Data number, indicated value and units
- Limit Settings- User selectable % of target or high low values
- Buzzer and 3 LED warnings- Yellow (under), Green (within), Red (over)
- Weight: 8 oz [0.23 Kg]




ENVIRONMENT:

- Operating Temperature: 32 to 105°F [0 to 41°C]
- Storage Temperature: 32 to 105°F [0 to 41°C]
- Relative Humidity: 0 / 95° non-condensing

STOCK #S

- STK# FSH01439- Torque Display (ft-lb, in-lb, in-oz, N-m, cN-m, Kgf-m)
- STK# FSH01906- Load Display (lb,N,Kn,Kg, g)



SCIGATE AUTOMATION (S) PTE LTD
 No.1 Bukit Batok Street 22 #01-01 Singapore 659592
 Tel: (65) 6561 0488 Fax: (65) 6562 0588
 Email: sales@scigate.com.sg Web: www.scigate.com.sg
 Business Hours: Monday - Friday 8.30am - 6.15pm



This drawing is submitted solely for the information and exclusive use of the original addressee. It is not to be divulged in whole or in part, by any firm or individual without written permission from FUTEK
 CAGE CODE # 1X8M6

10 THOMAS
 IRVINE, CA 92618 USA
 1-800-23-FUTEK (38835)

INTERNET:
<http://www.futek.com>