

FUTEK MODEL MBA400

BI-AXIAL LOAD ARM

(PREVIOUSLY L3010)


Drawing Number: FI1230-A

INCH [mm] | R.O.= Rated Output

WIRING CODE (CC 4)

+Excitation -Excitation +Signal -Signal

RED BLACK GREEN WHITE



4 x #8-32 X 0.25 [6.4] DEEP
EQUALLY SPACED ON
1.25 [31.8] B.C.D. (FAR SIDE)

#8-32 X 0.37 [9.4] DEEP

2 x 0.34 FLAT [8.8]

Ø0.75 [Ø19.0]

0.70 [17.9]

Ø0.80 [Ø20.3]

0.35 (REF LOADING POINT)

3.32 [84.3]

1.25 [31.8]

0.32 [8.1]

(2) LEMO RECEPTACLE
EGG.OB.304.CLL
MATING CONNECTOR
FGG.OB.304.CLAD35
(NOT INCLUDED)

1/4-28-2B THRU

Ø0.75 [Ø19.1] X
0.92 [23.2] DEEP

Ø1.98 [Ø50.3]

SPECIFICATIONS:

RATED OUTPUT

CAPACITY

SAFE OVERLOAD

ZERO BALANCE

EXCITATION (VDC OR VAC)

BRIDGE RESISTANCE

NONLINEARITY

TEMP. SHIFT ZERO

TEMP. SHIFT SPAN

COMPENSATED TEMP.

OPERATING TEMP.

WEIGHT

MATERIAL

CONNECTOR: 4 Pin Lemo Receptacle (EGG.OB.304.CLL)

ACCESSORIES AND RELATED INSTRUMENTS AVAILABLE

CALIBRATION (STD) FX and FY

CALIBRATION (AVAILABLE)

CALIBRATION TEST EXCITATION

SEE CHART

SEE CHART

150% of R.O.

1% of R.O.

18 MAX

350 Ω nom.

±0.1% of R.O.

±0.025% of R.O./F° (0.045% of R.O./C°)

±0.01% of LOAD/F (0.018% of LOAD /C°)

60 to 160°F (16 to 71°C)

-60 to 200°F (-51 to 93°C)

16 oz (454 g)

STAINLESS STEEL

5 pt TENSION; 60.4K Ω (50 lb), 43.575K Ω (200 lb) SHUNT CAL. VALUE

COMPRESSION

10 VDC

STOCK NO:	CAPACITIES		R.O. (nom.)
	lb	N	
FSH01071	50	223	2 mV/V
FSH01070	200	890	3 mV/V

**SCIENCE
GATE**
Your Automation Partner



SCIGATE AUTOMATION (S) PTE LTD

No.1 Bukit Batok Street 22 #01-01 Singapore 659592

Tel: (65) 6561 0488

Fax: (65) 6562 0588

Email: sales@scigate.com.sg

Web: www.scigate.com.sg

Business Hours: Monday - Friday 8.30am - 6.15pm

FUTEK
ADVANCED SENSOR TECHNOLOGY, INC.

This drawing is submitted solely for the information and exclusive use of the original addressee. It is not to be divulged in whole or in part, by any firm or individual without written permission from FUTEK

10 THOMAS
IRVINE, CA 92618 USA
1-800-23-FUTEK (38835)

INTERNET:
<http://www.futek.com>