
FUTEK MODEL ZCC994 ITEM #: FSH03669

_____ FOR

12 Pin Binder To 8 & 6 Pin Screw Terminal Cable Assembly FOR FUTEK MODEL IPM650


Drawing Number: FI1343

INCH [mm]



PIN	WIRING CODE (CABLE 1)	
Α	+EXCITATION (RED)	
В	+SIGNAL (GREEN)	
С	-EXCITATION (BLACK)	
D	-SIGNAL (WHITE)	
Е	TEDS (ORANGE)	
G	GROUND (BLUE)	

PIN	WIRING CODE (CABLE 2)	
F	24V OUT (ORANGE)	
G	GROUND (BLUE & BLACK)	
Н	5V OUT (RED)	
J	-VOLTAGE INPUT (WHITE)	
K	+VOLTAGE INPUT (GREEN)	



MOUNTING CUTOUT	CABLE	SPECIFICATIONS
Ø.709 [Ø18.0]	28 AWG, 6 CONDUCTOR BRAIDED SHIELDED POLYURETHANE DIAMETER: 0.165 [4.2]	TEMP: -40° to 176°F [-40° to 80°C]
0.406 [10.3]	CABLE MINIMUM BEND RADIUS: 1.65 [41.9]	IP RATING IP67*
PANEL THICKNESS: MIN. 0.039 [1.0] MAX. 0.157 [4.0]		

^{*} When mated with connector



This drawing is submitted solely for the information and exclusive use of the original addressee. It is not to be divulged in whole or in part, by any firm or individual without written permission from FUTEK

CAGE CODE # 1X8M6

10 THOMAS IRVINE, CA 92618 USA 1-800-23-FUTEK (38835)

INTERNET: http://www.futek.com