



## TYPE: TCA



# TCA Stainless Steel Tension & Compression Load Cell

## Description

The TCA series load cell is ideal for measuring both tensile and compressive forces. The standard metric threads at each end of the load cell are designed to accept standard spherical seating rod-end bearings.

There is great flexibility in the TCA design, allowing us to offer special sizes to meet specific application requirements, or different end thread sizes/combinations. There are versions available with male threads at each end, or male threads at one end and female at the other. We are also happy to supply any of the TCA series with imperial thread sizes.

The TCA series can be supplied as shown in this datasheet or can be modified to meet a particular application requirement. We are always pleased to discuss any special requirements that can be accommodated.

The TCA series can be supplied on its own or combined with our extensive range of instrumentation to provide a complete load monitoring system.

## Features

- Ranges from 1 to 150 tonnes
- Stainless steel construction
- Special sizes and ranges available
- Can be supplied with imperial threads & male or male/female end threads
- Can be supplied complete with mating spherical rod-end bearings\*
- Environmentally sealed to IP66 (IP67 and submersible versions are also available)

\* Our 1, 3, 5 and 7.5 tonne versions can be used with standard rod end bearings. All other capacities require heavy duty rod end bearings. Please contact a member of the LCM Sales Team if these are required.

## Specification

|                                |  |  |
|--------------------------------|--|--|
| Rated load (tonnes)            | 1, 2, 3, 5, 7.5, 10, 20, 30, 50, 75, 100, 150                                  |  |
| Proof load                     | 150% of rated load   |  |
| Ultimate breaking load         | >300% of rated load  |  |
| Output                         | 1.5mV/V nominal  |  |
| Accuracy                       | <±0.2% of rated load   |  |
| Non-repeatability              | <±0.1% of rated load   |  |
| Excitation voltage             | 10vdc recommended, 15vdc maximum   |  |
| Bridge resistance              | 1te: 350Ω, 2 to 50te: 700Ω, 75 to 150te: 1400Ω                                 |  |
| Insulation resistance          | >500MΩ @ 500vdc  |  |
| Operating temperature range    | -20 to +70°C (-20 to +55°C for Ex d versions)                                  |  |
| Compensated temperature range  | -10 to +50°C   |  |
| Zero temperature coefficient   | <±0.01% of rated load/°C   |  |
| Span temperature coefficient   | <±0.01% of rated load/°C   |  |
| ATEX certification details     | Ex i   | II 2G Ex ib IIC T4 Gb / II 2D Ex ib IIIC T135°C Db |
|                                | Ex d   | II 2G Ex d IIC T6 Gb / II 2D Ex tb IIIC T85°C Db   |
| Environmental protection level | IP66 (IP67 optional)   |  |
| Connection type                | Integrated bayonet lock connector, supplied with 5 metre mating cable assembly |  |
| Wiring connections             | +supply: Red   | -supply: Blue                                      |
|                                | +signal: Green   | -signal: Yellow                                    |

## Typical Applications

- Structural testing
- Jack load monitoring
- Cable tension monitoring
- Material test machine feedback
- Press load monitoring

## Available Options

- Special ranges and sizes available
- Different thread arrangements
- Hazardous Area certified - Explosion Proof (Ex d) and Intrinsically Safe (Ex i)
- Special electrical connections
- Submersible versions available
- TEDS option when used with TR150 handheld display (Not available with Hazardous Area versions)



SCIGATE AUTOMATION (S) PTE LTD


No 1 Bukit Batok Street 22 #01-01 Singapore 659592  
Tel: (65) 6561 0488 Fax: (65) 6561 0588  
Email: sales@scigate.com.sg Web: https://scigate.com.sg/

Business Hours: Monday - Friday 8:30AM - 6:15PM



# TCA Stainless Steel Tension & Compression Load Cell

## Dimensions



All dimensions are in mm

| Rating (tonnes) | B   | C   | $\varnothing D$ | Thread T   | Weight (kgs) | Resolution (tonnes) |
|-----------------|-----|-----|-----------------|------------|--------------|---------------------|
| 1               | 76  | 16  | 31              | M12 x 1.25 | 0.4          | 0.001               |
| 2               | 76  | 16  | 31              | M12 x 1.25 | 0.4          | 0.002               |
| 3               | 84  | 22  | 38              | M20 x 1.5  | 0.7          | 0.005               |
| 5               | 84  | 22  | 38              | M20 x 1.5  | 0.7          | 0.005               |
| 7.5             | 108 | 29  | 44              | M24 x 2    | 1.3          | 0.01                |
| 10              | 108 | 29  | 44              | M24 x 2    | 1.3          | 0.01                |
| 20              | 203 | 50  | 57              | M36 x 3    | 3.3          | 0.02                |
| 30              | 355 | 89  | 114             | M64 x 4    | 20           | 0.02                |
| 50              | 355 | 89  | 114             | M64 x 4    | 20           | 0.05                |
| 75              | 458 | 100 | 130             | M100 x 3   | 35.7         | 0.05                |
| 100             | 458 | 100 | 130             | M100 x 3   | 35.7         | 0.1                 |
| 150             | 458 | 100 | 156             | M100 x 3   | 40.5         | 0.2                 |

**Note 1:** Default calibration of load cells rated up to 20 tonnes will be in tension. TCAs rated 30 tonnes and above will be in compression. If you require calibration in a different mode to the standard or in both tension & compression, please state at time of order (additional charges may apply).

**Note 2:** Part numbers for ATEX versions will be suffixed with either -ATEX-D (explosion proof) or -ATEX-I (intrinsically safe) e.g. TCA-75-D-ATEX-D.

**Note 3:** Dimensions may change for hazardous area versions.



www.lcmsystems.com

**LCM Systems Ltd**

Unit 15, Newport Business Park, Barry Way  
Newport, Isle of Wight PO30 5GY UK  
Tel: +44 (0)1983 249264  
sales@lcm systems.com  
www.lcm systems.com

**LCM Systems (România)**

Strada Ștefan Cel Mare 26a,  
Tunari, cod.077180, Ilfov, România  
Tel: +40 (0)77 4641899  
ro@lcm systems.com  
www.lcm systems.ro

Due to continual product development, LCM Systems Ltd reserves the right to alter product specifications without prior notice.

**Issue No. 5**

Issue date: 03/02/2021  
APPROVED  
(unapproved if printed)