	YASKAWA VIPA CONTROLS	
Data sheet	SCIENCE Your Automation Partner	
- (900-2C520)	SCIGATE AUTOMATION (S) PTE LTD No.1 Bukit Batok Street 22 #01-01 Singapore 659592	
Technical data	Tel: (65) 6561 0488 Fax: (65) 6562 0588 Email: sales@scigate.com.sg Web: www.scigate.com.sg Business Hours: Monday - Friday 8.30am - 6.15pm	
Order no.	900-2C520	
Туре	-	
General information		
Note	-	
Features	WIFI interface for connection to a WIFI network 4x RJ45 LAN 100 Mbit/s (configurable LAN/WAN) 2x digital input for internet release 1x digital output for display Talk2M integrated web interface for configuration OpenVPN for save internet connection with Talk2M high level protection through access control	
Inputs and outputs		
Inputs	-	
Outputs		
Communication		
serial port	USB	
LAN	-	
WAN	-	
Modem type	-	
Router		
Router functions	Talk2M	
RAS	-	
VPN		
VPN mode	-	
Talk2M	-	
Gateway protocols	-	
Services		
Server services	ЕТР НТТР	
Client Services	NTP SNMP V1	
Data management		
Custom Website	-	
Project	web interface	
Integrated protocols	-	
Interrupts		
Alarm message	-	
Alarm	-	
Housing		
Material		

YASKAWA VIPA CONTROLS

Mounting	Profile rail 35 mm	
Mechanical data		
Dimensions (WxHxD)	42.6 mm x 107.8 mm x 98.3 mm	
Net weight	202 g	
Weight including accessories	-	
Gross weight	-	
Environmental conditions		
Operating temperature	-20 °C to 70 °C	
Storage temperature	-40 °C to 70 °C	
Certifications		
UL certification	yes	
KC certification	yes	