



SCIGATE AUTOMATION (S) PTE LTD

No.1 Bukit Batok Street 22 #01-01 Singapore 659592
 Tel: (65) 6561 0488 Fax: (65) 6562 0588
 Email: sales@scigate.com.sg Web: www.scigate.com.sg
 Business Hours: Monday - Friday 8.30am - 6.15pm

Data sheet
TM-C Router (900-2C610)

Technical data

Order no.	900-2C610
Type	TM-C Router
General information	
Note	-
Features	For teleservice through broadband connection via Talk2M 1x RS485 MPI-/PROFIBUS-DP interface 4x LAN RJ45 Ethernet interface 1x WAN RJ45 Ethernet interface
Inputs and outputs	
Inputs	1 DI: 0/24 V DC, isolated
Outputs	1 DO: open drain, max. 200 mA at DC 30 V
Communication	
serial port	MPI/PROFIBUS, isolated, up to 12 MBit/s
LAN	4 x RJ45, 10/100 MBit/s Switch
WAN	1 x RJ45, 10/100 MBit/s
Modem type	-
Router	
Router functions	Talk2M
RAS	-
VPN	
VPN mode	-
Talk2M	yes
Gateway protocols	-
Services	
Server services	FTP HTTP
Client Services	-
Data management	
Custom Website	yes
Project	web interface
Integrated protocols	-
Interrupts	
Alarm message	-
Alarm	-
Housing	
Material	-
Mounting	Profile rail 35 mm
Mechanical data	

Dimensions (WxHxD)	39 mm x 129 mm x 108 mm
Net weight	410 g
Weight including accessories	-
Gross weight	-

Environmental conditions

Operating temperature	-20 °C to 70 °C
Storage temperature	-25 °C to 70 °C

Certifications

UL certification	-
KC certification	-